

Model: PFSE51A

Features:

Submersible sewage pumps designed for typical raw sewage applications.

- **DISCHARGE:** 2" NPT, Female, Vertical, Bolt-on Flange
- **LIQUID TEMPERATURE:** 104°F Continuous
- **MOTOR HOUSING/ VOLUTE:** Cast Iron, Class 30
- **IMPELLER:** 2 vane, Open type , Cast Iron, Class 30
- **SHAFT & HARDWARE:** Stainless steel
- **SEAL PLATE:** Cast Iron, Class 30
- **PAINT:** Industrial grade powder coating
- **O-RINGS:** Buna-N
- **SEAL:** Inboard, Single mechanical, .625 inch, Oil Filled reservoir, Carbon/Ceramic/Buna-N with Secondary Exclusion Seal
- **UPPER BEARING:** Single row, ball, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 15ft., SJTOW, 14/3 Cord with plug, Fast disconnect design
- **MOTOR:** Class B Insulation, Oil Filled, Squirrel Cage Induction
- **SINGLE PHASE:** Permanent Split Capacitor (PSC), Includes overload protection in motor
- **LEVEL CONTROL:** Wide Angle, Mechanical, Normally Open (N/O), 16/2, SJOW cord with Piggy-Back plug. 3.50" Min. Tether, On-Off Adjustable, P/N: PF101758.
- **WARRANTY:** 2 year

 **WARNING:** CANCER AND REPRODUCTIVE HARM-
WWW.P65WARNINGS.CA.GOV



**Submersible Sewage
2" Discharge,
2" Spherical Solids
Wide Angle Float**



MODEL	HP	VOLTS/ PHASE	HZ	RPM	FULL LOAD AMPS	LOCKED ROTOR AMPS	NEMA START CODE	CORD SIZE	CORD TYPE	Simplex Control	Duplex Control
PFSE51A	0.5	115/1	60	1750	11.6	21.3	E	14/3	SJTOW	n/a	n/a

2" to 3" Adapter Flange **P/N: PFDSCF0962**



Power-Flo Pumps & Systems

a Power-Flo Technologies company

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

2" - Sewage Pumps - PFSE, 1/2HP - 1750RPM - 60Hz

Model: PFSE51A

2" - Sewage Pumps - PFSE, 1/2HP, 1750RPM - 60HZ

